



PrH

PRODUCT HANDLING

WATER SPRAY RETORTS



Retort Versatility Processes Everything From Cans To Pouches

The simplest way to take advantage of the popularity of new flexible and semi-rigid types of shelf-stable containers. Allpax water spray retorts utilize 9 spray bars -3 on top and 6 on the sides. Additionally, direct injection steam heating both above and below the waterline provides heat to the retort load from the bottom, top and sides. Also available as dual-mode with saturated steam processing capability the flexibility of processing cans is afforded. Adding the Gentle Motion agitation option for water spray retorts is a low cost way to shorten cycle time vs. traditional static processing.

FEATURES AND BENEFITS

- High-volume pump provides high flow rates and ultra-efficient processing
- Most cost-effective method (cost/capacity ratio) of providing air overpressure for new containers
- Can be outfitted with either the space-saving Allpax automatic overhead orbiting door or swing-open door
- Same durable 304 stainless steel construction
- Chain conveyor basket loading is available in longer machine lengths
- Fully automated process control—Allpax Monitor recipe editor and report generator and AllView HMI interface

©2018 ProMach Inc. ProMach reserves the right to change or discontinue specifications and designs shown in this brochure without notice or recourse

PHONE
985-893-9277

EMAIL
Allpax@ProMachBuilt.com

WEB
Allpax.com

13510 Seymour Myers Blvd.
Covington, LA 70433